

View Online at <https://aerobasegroup.com/nsn/5905-01-628-7524>

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Body Diameter:

Between 24.1 millimeters and 25.1 millimeters

Shaft Diameter:

6.0 millimeters

Shaft Length:

20.0 millimeters

Mounting Bushing Length:

Between 9.0 millimeters and 11.0 millimeters

Body Length:

Between 12.5 millimeters and 14.5 millimeters

Shaft Style:

Round, t slotted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

Between 295.0 and 305.0

Screw Thread Diameter:

9.0 millimeters

Screw Thread Series Designator:

Iso m

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

100.0 ohms single section

Power Dissipation Rating Per Section In Watts:

0.25 free air single section

Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 single section

Actuator Travel Control Feature:

Stops

Product Name:

Carbon potentiometer

Special Features:

Panel mount, single unit, single shaft, right angle ear-lug terminals; metal shaft and bushing; shaft length: 20mm; low torque

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0