Inductive Wire Wound Fixed Resistor - Page 1 of 1

View Online at https://aerobasegroup.com/nsn/5905-01-629-9724

# Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:

-100.0 to 100.0

## **Electrical Resistance:**

249.0 ohms

### **Resistance Tolerance In Percent:**

-1.0 to 1.0

## Ambient Tempurature In Deg Celsius At Full Rated Power:

#### 70.0

### Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

155.0

#### **Inclosure Method:**

Encased

#### **Terminal Type:**

Tab, solder lug

### **Reactance Characteristic:**

Inductive

#### **Reliability Indicator:**

Not established

# **Terminal Length:**

0.563 inches

### **Body Diameter:**

0.563 inches

### **Body Length:**

2.000 inches

### **Power Dissipation Rating In Watts:**

0.125 free air

### **Unable To Decode:**

0.250 inches

### **Product Name:**

Wirewound resistor, industrial power, tubula (inductive)

#### **Special Features:**

Skin pack; material: element: copper-nickel alloy; core: ceramic, steatite; coating: high temperature silicone; terminal bands: steel;

terminal finish: tin/lead

### Style Designator:

Axial terminal each end

## Shelf Life:

N/a

# Unit Of Measure:

--

## **Demilitarization:**

No

# Fiig:

A001a0

