## NSN 5905-01-631-5289

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-01-631-5289

| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:   |
|---|
| -100.0 to 100.0   |
|   |
| Electrical Resistance:  |
| 100.0 ohms  |
| Resistance Tolerance In Percent:  |
| -2.0 to 2.0   |
| Ambient Tempurature In Deg Celsius At Full Rated Power:   |
| 70.0  |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:   |
| 150.0   |
| Inclosure Method:   |
| Encapsulated  |
| Terminal Type:  |
| Wire lead   |
| Reliability Indicator:  |
| Not established   |
| Terminal Length:  |
| Between 1.060 inches and 1.140 inches   |
| Body Diameter:  |
| Between 0.082 inches and 0.098 inches   |
| Body Length:  |
| Between 0.225 inches and 0.265 inches   |
| Power Dissipation Rating In Watts:  |
| 0.25 free air   |
| Unable To Decode:   |
| Between 0.021 inches and 0.025 inches   |
| Product Name:   |
| Ccf07 metal film resistors, industrial, 2% tolerance  |
| Special Features:   |
| Dual power rating: 0.25 w with 1.5% stability and 0.50 w with 2.0% stability; rohs compliant; tape and reel packaging, 5000 pieces; flame |
| retardant epoxy conformal coating (red brown color); standard 4 band color code; lead (pb)-free terminals with pure tin coating           |
| Style Designator:   |
| Axial terminal each end   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A001a0  |