

View Online at https://aerobasegroup.com/nsn/5910-00-001-2992

| Ded. 0 | |
|----------|---|
| Body S | |
| Chip typ | |
| | lity Indicator: |
| | ablished |
| Body L | |
| 0.095 in | |
| Body W | |
| 0.050 in | |
| Body H | - |
| 0.050 in | nches |
| Schem | atic Diagram Designator: |
| No com | nmon or grounded electrode (s) |
| Capacit | tance Value Per Section: |
| 3.900 p | icofarads single section |
| Nonder | rated Operating Temp: |
| Betwee | n -55.0 degrees celsius and 125.0 degrees celsius |
| Tempu | rature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: |
| 0.0 sing | gle section |
| Nonder | rated Continuous Voltage Rating And Type Per Section: |
| 50.0 dc | single section |
| Tolerar | nce Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: |
| -25.0/+2 | 25.0 single section |
| Tolerar | nce Range Per Section: |
| -0.50/+(| 0.50 picofarads single section |
| Case M | laterial: |
| Cerami | c |
| Insulati | ion Resistance At Reference Temp: |
| 100000 | .0 megohms |
| Dissipa | ation Factor At Reference Tempurature In Percent: |
| 0.1000 | |
| Termin | al Surface Treatment: |
| Silver | |
| Termin | al Type And Quantity: |
| 2 bondii | |
| Shelf L | |
| N/a | |
| Unit Of | Measure: |
| | |
| Demilit | arization: |
| No | |
| Fiig: | |
| A010b0 | |