

View Online at https://aerobasegroup.com/nsn/5910-00-001-3022

Body Style:

W/o mtg facilities, axial terminals

Reliability Indicator:

Not established

Terminal Length:

1.500 inches

Body Diameter:

0.393 inches

Body Length:

0.629 inches

Terminal Diameter:

0.025 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

End Application:

2m/ate microminiauture automatic test equipment; nimitz class cvn; emory s. Land class as; tarawa class lha; arleigh burke class ddg; ticonderoga class cg (47)

Capacitance Value Per Section:

10000.000 picofarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

63.0 dc single section

Criticality Code Justification:

Feat

Tolerance Range Per Section:

-1.00/+1.00 percent single section

Case Material:

Plastic

Terminal Surface Treatment:

Solder

Dielectric Material:

Plastic polystyrene

Special Features:

Weapon system essential

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

NSN 5910-00-001-3022

Plastic Dielectric Fixed Capacitor - Page 2 of 2

Fiig: A010b0

