## NSN 5910-00-001-3177

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-001-3177 **Body Style:** W/o mtg facilities terminal (s) on one surface **Reliability Indicator:** Not established **Terminal Length:** 2.250 inches **Body Length:** 0.325 inches **Body Width:** 0.225 inches **Body Height:** 0.125 inches Center To Center Distance Between Terminals Parallel To Length: 0.290 inches **Terminal Diameter:** 0.025 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Insulation Resistance At Maximum Operating Temp:** 4000.0 megohm-microfarads **Capacitance Value Per Section:** 1000.000 picofarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section **Tolerance Range Per Section:** -5.00/+5.00 percent single section **Case Material: Plastic Insulation Resistance At Reference Temp:** 40000.0 megohm-microfarads **Power Factor At Reference Tempurature In Percent:** 1.0000 **Terminal Surface Treatment:** Solder **Terminal Type And Quantity:** 2 uninsulated wire lead Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5910-00-001-3177

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



_		••	• •					
וו	em	ш	112	r17	2+	$\sim$	n	
$\boldsymbol{-}$	CIII	••	ıιa	114	.aı	ı		

No

Fiig:

A010b0