

View Online at <https://aerobasegroup.com/nsn/5910-00-001-5805>

Body Style:

Rotary

Terminal Length:

0.250 inches

Overall Height:

0.156 inches

Overall Diameter:

0.200 inches

Temperature Coefficient Of Capacitance In Ppm Per Deg Celsius:

-250.0 single section

Temperature Coefficient Of Capacitance Range In Ppm Per Deg Celsius:

-250.0 to 250.0 single section

Center To Center Distance Between Terminals Parallel To Diameter:

0.125 inches

Terminal Diameter:

0.042 inches

Quality Factor At 25 Deg Celsius:

500.0

Fragility Factor:

Moderately rugged

Inclosure Type:

Encased

Adjustment Device Torque:

Between 0.500 inch-ounces and 5.000 inch-ounces

Insulation Dc Resistance At 25 Deg Celsius:

10000.0 megohms

Mounting Facility Type And Quantity:

2 terminal

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Capacitance Range In Picofarads:

+3.5 to 20.0 single section

Nonderated Voltage Rating And Type:

50.0 dc continuous single section

Adjustment Device Drive Type And Quantity:

1 slotted screw

Capacitance Drift In Picofarads:

0.50 single section

Material:

Ceramic capacitive electrode

Precious Material And Location:

Terminal surfaces gold

Precious Material:

Gold

Terminal Type And Quantity:

2 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A096a0