## NSN 5910-00-004-5899

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-004-5899

## Body Style:

W/o mtg facilities, axial terminals

## Mil-std-1276 Wire Lead Type Designator:

N-2

**Reliability Indicator:** 

Not established

## **Terminal Length:**

1.500 inches

#### **Body Diameter:**

0.332 inches

**Body Length:** 

0.843 inches

## Schematic Diagram Designator:

No common or grounded electrode (s)

#### **Capacitance Value Per Section:**

0.470 microfarads single section

## Nonderated Operating Temp:

Between -55.0 degrees celsius and 105.0 degrees celsius

## Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

200.0 single section

## Nonderated Continuous Voltage Rating And Type Per Section:

50.0 dc single section

## **Tolerance Range Per Section:**

-1.00 to 1.00 percent single section

#### **Case Material:**

Metal

## **Dissipation Factor At Reference Tempurature In Percent:**

0.2500

**Terminal Surface Treatment:** 

Gold

## **Case Insulation Material:**

Plastic

## **Special Test Features:**

Burn-in

## Terminal Type And Quantity:

2 uninsulated wire lead

## Shelf Life:

N/a

## Unit Of Measure:

---

## Demilitarization:

No

# NSN 5910-00-004-5899

Plastic Dielectric Fixed Capacitor - Page 2 of 2

**Fiig:** A010b0

