

View Online at <https://aerobasegroup.com/nsn/5910-00-004-5922>

Body Style:

W/mtg hol (s)/slot(s) terminal(s) on one surface

Reliability Indicator:

Not established

Body Length:

6.000 inches

Body Width:

2.120 inches

Body Height:

1.500 inches

Center To Center Distance Between Terminals Parallel To Length:

5.500 inches

Terminal Height From Body:

0.300 inches

Unthreaded Mounting Hole Diameter:

0.187 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

5.250 inches

Schematic Diagram Designator:

Series connected

Mounting Facility Type And Quantity:

2 unthreaded mounting holes

Section Quantity:

2

Insulation Resistance At Maximum Operating Temp:

350.0 megohm-microfarads

Capacitance Value Per Section:

0.040 microfarads all sections

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

10000.0 dc all sections

Temperature Coefficient Of Capacitance Range Per Section In Ppm Per Deg Celsius:

-3.0 to 5.0 all sections

Tolerance Range Per Section:

-10.00 to 10.00 percent all sections

Case Material:

Plastic

Insulation Resistance At Reference Temp:

8000.0 megohm-microfarads

Dissipation Factor At Reference Temperature In Percent:

0.600

Terminal Surface Treatment:

Solder

Terminal Type And Quantity:

3 standoff, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0