

View Online at <https://aerobasegroup.com/nsn/5910-00-004-6195>

Body Style:

W/thd mtg bushing, terminals on opposite ends

Mil-std-1276 Wire Lead Type Designator:

D

Reliability Indicator:

Not established

Width Across Flats:

0.250 inches

Body Length:

0.468 inches

Schematic Diagram Designator:

Feedthrough

Mounting Facility Screw Thread Series Designator:

Unf

Mounting Facility Type And Quantity:

1 threaded bushing

Features Provided:

Mounting hardware

Capacitance Value Per Section:

100.000 picofarads single section

Voltage Temperature Limits Per Section In Percent Capacitance Change:

-15.0 to 15.0 without voltage applied single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Thread Size:

0.216 inches

Nonderated Continuous Voltage Rating And Type Per Section:

500.0 dc single section

Tolerance Range Per Section:

-10.00 to 10.00 percent single section

Case Material:

Metal

Power Factor At Reference Temperature In Percent:

2.0000

Terminal Surface Treatment:

Gold

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A010b0