Mica Dielectric Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-00-005-3797

Reliability Indicator:   Not established   Terminal Length:   1.500 inches   Body Width:   0.340 inches   Center To Center Distance Between Terminals Parallel To Length:   0.141 inches   Insulation Resistance At Maximum Operating Temp:   20000.0 megohms   Unable To Decode:   Between -55.0 degrees celsius and unable to decode   Tempurature Coefficient Of Capacitance Range Per Section In Ppm Per Deg Celsius:   -20.0 to 100.0 single section   Case Material:   Plastic   Insulation Resistance At Reference Temp:   10000.0 megohms   Terminal Surface Treatment:   Solder   Shelf Life:   N/a
Terminal Length: 1.500 inches Body Width: 0.340 inches Center To Center Distance Between Terminals Parallel To Length: 0.141 inches Insulation Resistance At Maximum Operating Temp: 20000.0 megohms Unable To Decode: Between -55.0 degrees celsius and unable to decode Tempurature Coefficient Of Capacitance Range Per Section In Ppm Per Deg Celsius: -20.0 to 100.0 single section Case Material: Plastic Insulation Resistance At Reference Temp: 100000.0 megohms Terminal Surface Treatment: Solder Shelf Life:
1.500 inches Body Width: 0.340 inches Center To Center Distance Between Terminals Parallel To Length: 0.141 inches Insulation Resistance At Maximum Operating Temp: 20000.0 megohms Unable To Decode: Between -55.0 degrees celsius and unable to decode Tempurature Coefficient Of Capacitance Range Per Section In Ppm Per Deg Celsius: -20.0 to 100.0 single section Case Material: Plastic Insulation Resistance At Reference Temp: 100000.0 megohms Terminal Surface Treatment: Solder Shelf Life:
Body Width: 0.340 inches Center To Center Distance Between Terminals Parallel To Length: 0.141 inches Insulation Resistance At Maximum Operating Temp: 20000.0 megohms Unable To Decode: Between -55.0 degrees celsius and unable to decode Tempurature Coefficient Of Capacitance Range Per Section In Ppm Per Deg Celsius: -20.0 to 100.0 single section Case Material: Plastic Insulation Resistance At Reference Temp: 100000.0 megohms Terminal Surface Treatment: Solder Shelf Life:
0.340 inches Center To Center Distance Between Terminals Parallel To Length: 0.141 inches Insulation Resistance At Maximum Operating Temp: 20000.0 megohms Unable To Decode: Between -55.0 degrees celsius and unable to decode Tempurature Coefficient Of Capacitance Range Per Section In Ppm Per Deg Celsius: -20.0 to 100.0 single section Case Material: Plastic Insulation Resistance At Reference Temp: 100000.0 megohms Terminal Surface Treatment: Solder Shelf Life:
Center To Center Distance Between Terminals Parallel To Length: 0.141 inches Insulation Resistance At Maximum Operating Temp: 20000.0 megohms Unable To Decode: Between -55.0 degrees celsius and unable to decode Tempurature Coefficient Of Capacitance Range Per Section In Ppm Per Deg Celsius: -20.0 to 100.0 single section Case Material: Plastic Insulation Resistance At Reference Temp: 100000.0 megohms Terminal Surface Treatment: Solder Shelf Life:
0.141 inches Insulation Resistance At Maximum Operating Temp: 20000.0 megohms Unable To Decode: Between -55.0 degrees celsius and unable to decode Tempurature Coefficient Of Capacitance Range Per Section In Ppm Per Deg Celsius: -20.0 to 100.0 single section Case Material: Plastic Insulation Resistance At Reference Temp: 100000.0 megohms Terminal Surface Treatment: Solder Shelf Life:
Insulation Resistance At Maximum Operating Temp: 20000.0 megohms Unable To Decode: Between -55.0 degrees celsius and unable to decode Tempurature Coefficient Of Capacitance Range Per Section In Ppm Per Deg Celsius: -20.0 to 100.0 single section Case Material: Plastic Insulation Resistance At Reference Temp: 100000.0 megohms Terminal Surface Treatment: Solder Shelf Life:
20000.0 megohms Unable To Decode: Between -55.0 degrees celsius and unable to decode Tempurature Coefficient Of Capacitance Range Per Section In Ppm Per Deg Celsius: -20.0 to 100.0 single section Case Material: Plastic Insulation Resistance At Reference Temp: 100000.0 megohms Terminal Surface Treatment: Solder Shelf Life:
Unable To Decode: Between -55.0 degrees celsius and unable to decode Tempurature Coefficient Of Capacitance Range Per Section In Ppm Per Deg Celsius: -20.0 to 100.0 single section Case Material: Plastic Insulation Resistance At Reference Temp: 100000.0 megohms Terminal Surface Treatment: Solder Shelf Life:
Between -55.0 degrees celsius and unable to decode Tempurature Coefficient Of Capacitance Range Per Section In Ppm Per Deg Celsius: -20.0 to 100.0 single section Case Material: Plastic Insulation Resistance At Reference Temp: 100000.0 megohms Terminal Surface Treatment: Solder Shelf Life:
Tempurature Coefficient Of Capacitance Range Per Section In Ppm Per Deg Celsius: -20.0 to 100.0 single section Case Material: Plastic Insulation Resistance At Reference Temp: 100000.0 megohms Terminal Surface Treatment: Solder Shelf Life:
-20.0 to 100.0 single section Case Material: Plastic Insulation Resistance At Reference Temp: 100000.0 megohms Terminal Surface Treatment: Solder Shelf Life:
Case Material: Plastic Insulation Resistance At Reference Temp: 100000.0 megohms Terminal Surface Treatment: Solder Shelf Life:
Plastic Insulation Resistance At Reference Temp: 100000.0 megohms Terminal Surface Treatment: Solder Shelf Life:
Insulation Resistance At Reference Temp: 100000.0 megohms Terminal Surface Treatment: Solder Shelf Life:
100000.0 megohms Terminal Surface Treatment: Solder Shelf Life:
Terminal Surface Treatment: Solder Shelf Life:
Solder Shelf Life:
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A010b0