## NSN 5910-00-006-7438

**Specification Data:** 

81349-mil-c-19978/3 government specification

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-006-7438

**Body Style:** W/o mtg facilities, terminal (s) on one surface **Reliability Indicator:** Not established **Body Length:** 1.812 inches **Body Width:** 1.062 inches **Body Height:** 2.250 inches **Center To Center Distance Between Terminals Parallel To Length:** 0.813 inches **Terminal Height From Body:** 1.375 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Features Provided:** Hermetically sealed case **Insulation Resistance At Maximum Operating Temp:** 300.0 megohm-microfarads **Capacitance Value Per Section:** 2.000 microfarads single section **Nonderated Operating Temp:** Between -65.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 600.0 dc single section **Tolerance Range Per Section:** -10.00/+10.00 percent single section **Case Material:** Metal **Insulation Resistance At Reference Temp:** 15000.0 megohm-microfarads **Dissipation Factor At Reference Tempurature In Percent:** 1.0000 **Dielectric Material:** Plastic **Test Data Document:** 81349-mil-c-19978 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 2 threaded stud

## NSN 5910-00-006-7438

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A010b0