## NSN 5910-00-007-0622

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-007-0622 **Body Style:** W/o mtg facilities, axial terminals Reliability Indicator: Not established **Terminal Length:** 2.375 inches **Body Diameter:** 0.145 inches **Body Length:** 0.656 inches **Schematic Diagram Designator:** Electrod (s) grounded to case, w/gnd terminal **Anode Type:** Solid **Impedance At Minimum Operating Tempurature In Ohms:** 170.0 **Electrical Polarization:** Polarized **Capacitance Value Per Section:** 70.000 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Dc Leakage At Maximum Operating Temp: 20.0 milliamperes Nonderated Continuous Voltage Rating And Type Per Section: 15.0 dc single section **Tolerance Range Per Section:** -15.00/+20.00 percent single section **Case Material:** Metal **Capacitive Electrode Material: Equivalent Series Resistance At Reference Tempurature In Ohms:** 5.00 Dc Leakage At Reference Temp: 7.000 microamperes **Terminal Surface Treatment:** Solder **Case Insulation Material: Plastic** 

**Terminal Type And Quantity:** 

2 uninsulated wire lead

## NSN 5910-00-007-0622

Electrolytic Fixed Capacitor - Page 2 of 2



She	lf I	Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0