

View Online at <https://aerobasegroup.com/nsn/5910-00-007-0771>

Body Style:

W/o mtg facilities, terminal (s) on one end/w/o mtg facilities, terminal(s) on one end/w/o mtg facilities, terminal(s) on one end

Reliability Indicator:

Not established/not established/not established

Body Diameter:

3.000 inches

Body Length:

5.125 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Anode Type:

Plain foil

Electrical Polarization:

Polarized

End Application:

Tactical data system, an/uva- (v); oliver perry class ffg; spruance class dd (963); virginia class cgn (41); ticonderoga class cgn (41) ; forrestal class cv; wasp class lhd; nimitz class cvn; kidd class ddg; emory s.Land class as

Capacitance Value Per Section:

64000.000 microfarads single section

Nonderated Operating Temp:

Between -40.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

25.0 dc single section

Criticality Code Justification:

Feat

Tolerance Range Per Section:

-10.00/+75.00 percent single section

Case Material:

Metal

Capacitive Electrode Material:

Aluminum

Equivalent Series Resistance At Reference Temperature In Ohms:

0.012

Case Insulation Material:

Plastic

Special Features:

Weapon system essential

Terminal Type And Quantity:

2 threaded hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A010b0