## NSN 5910-00-007-1910

**Body Style:** 

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-007-1910

W/mtg tabs/flanges, terminal (s) on one surface
Reliability Indicator:
Not established
Mounting Slot Width:
0.250 inches
Body Length:
10.500 inches
Body Width:
5.750 inches
Body Height:
4.880 inches
Center To Center Distance Between Terminals Parallel To Length:
6.250 inches
Terminal Height From Body:
1.593 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
10.500 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
2.000 inches
Mounting Facility Type And Quantity:
4 mounting slots
Capacitance Value Per Section:

## 1.500 microfarads single section

Nonderstad Onesetina Tenes

#### **Nonderated Operating Temp:**

Between -65.0 degrees celsius and 85.0 degrees celsius

#### Nonderated Continuous Voltage Rating And Type Per Section:

8500.0 dc single section

#### **Tolerance Range Per Section:**

-10.00/+10.00 percent single section

#### **Case Material:**

Metal

#### **Insulation Resistance At Reference Temp:**

10.0 megohms

#### **Dissipation Factor At Reference Tempurature In Percent:**

0.6000

#### **Terminal Type And Quantity:**

2 standoff, threaded stud

### Shelf Life:

N/a

# NSN 5910-00-007-1910

Plastic Dielectric Fixed Capacitor - Page 2 of 2



		• •			
ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A010b0