## NSN 5910-00-007-2139

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-007-2139 **Body Style:** W/o mtg facilities terminal (s) on one surface **Reliability Indicator:** Not established **Terminal Length:** 1.250 inches **Body Length:** 0.190 inches **Body Width:** 0.190 inches **Body Height:** 0.090 inches **Center To Center Distance Between Terminals Parallel To Length:** Between 0.185 inches and 0.215 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Capacitance Value Per Section:** 330.000 picofarads single section Voltage Tempurature Limits Per Section In Percent Capacitance Change: -25.0/+15.0 with rated voltage applied single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section **Tolerance Range Per Section:** -20.00 to 20.00 percent single section Case Material:

**Plastic** 

**Insulation Resistance At Reference Temp:** 

100000.0 megohm-microfarads

**Dissipation Factor At Reference Tempurature In Percent:** 

2.5000

**Test Data Document:** 

81349-milc11015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:** 

2 uninsulated wire lead

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No

## NSN 5910-00-007-2139

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



Fiig:

A010b0