NSN 5910-00-007-7458



Mica Dielectric Fixed Capacitor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5910-00-007-7458 **Body Style:** W/o mtg facilities terminal (s) on one surface **Reliability Indicator:** Not established **Terminal Length:** 1.250 inches **Body Length:** 0.470 inches **Body Width:** 0.390 inches **Body Height:** 0.210 inches Center To Center Distance Between Terminals Parallel To Length: Between 0.203 inches and 0.265 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Insulation Resistance At Maximum Operating Temp:** 20000.0 megohms **Capacitance Value Per Section:** 660.000 picofarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 150.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 300.0 dc single section Tempurature Coefficient Of Capacitance Range Per Section In Ppm Per Deg Celsius: +0.0 to 70.0 single section **Tolerance Range Per Section:** -1.00 to 1.00 percent single section **Case Material: Plastic Insulation Resistance At Reference Temp:** 100000.0 megohms **Quality Factor At Reference Temp:** 2000.0000 **Terminal Surface Treatment:** Solder **Terminal Type And Quantity:** 2 uninsulated wire lead Shelf Life: N/a

--

Unit Of Measure:

NSN 5910-00-007-7458

Mica Dielectric Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0