## NSN 5910-00-007-9224

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-007-9224

**Body Style:** 

W/o mtg facilities terminal (s) on one surface

**Reliability Indicator:** 

Not established

**Terminal Length:** 

1.250 inches

**Body Length:** 

0.290 inches

**Body Width:** 

0.190 inches

.....

**Body Height:** 

0.090 inches

**Center To Center Distance Between Terminals Parallel To Length:** 

Between 0.185 inches and 0.215 inches

**Schematic Diagram Designator:** 

No common or grounded electrode (s)

**Capacitance Value Per Section:** 

1800.000 picofarads single section

**Nonderated Operating Temp:** 

Between -55.0 degrees celsius and 150.0 degrees celsius

Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

0.0 single section

Nonderated Continuous Voltage Rating And Type Per Section:

50.0 dc single section

Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:

-30.0/+30.0 single section

**Tolerance Range Per Section:** 

-1.00 to 1.00 percent single section

Case Material:

Plastic

Insulation Resistance At Reference Temp:

100000.0 megohms

**Dissipation Factor At Reference Tempurature In Percent:** 

0.1500

**Terminal Surface Treatment:** 

Solder

**Test Data Document:** 

81349-milc39014/6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:** 

2 uninsulated wire lead

Shelf Life:

N/a

## NSN 5910-00-007-9224

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A010b0