Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-008-2590

## **Body Style:**

W/o mtg facilities terminal (s) on one surface

#### **Reliability Indicator:**

Not established

# **Terminal Length:**

1.250 inches

### **Body Length:**

0.500 inches

#### **Body Width:**

0.280 inches

#### **Body Height:**

#### 0.125 inches

### Center To Center Distance Between Terminals Parallel To Length:

0.400 inches

#### **Terminal Diameter:**

Between 0.019 inches and 0.021 inches

## Schematic Diagram Designator:

No common or grounded electrode (s)

# Capacitance Value Per Section:

2200.000 picofarads single section

## Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

### Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

0.0 single section

### Nonderated Continuous Voltage Rating And Type Per Section:

50.0 dc single section

### Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:

-100.0/+100.0 single section

### **Tolerance Range Per Section:**

-1.00/+1.00 percent single section

### **Case Material:**

Plastic

### Insulation Resistance At Reference Temp:

100000.0 megohms

### **Dissipation Factor At Reference Tempurature In Percent:**

0.3000

## **Terminal Surface Treatment:**

Solder

### **Dielectric Material:**

Plastic polyethylene terephthalate

# Terminal Type And Quantity:

2 uninsulated wire lead

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0