Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-008-2592

### Body Style:

W/o mtg facilities terminal (s) on one surface

**Reliability Indicator:** 

Not established

Terminal Length:

1.250 inches

Body Length:

0.500 inches

**Body Width:** 

0.280 inches

**Body Height:** 

0.125 inches

#### Center To Center Distance Between Terminals Parallel To Length:

Between 0.395 inches and 0.405 inches

#### Schematic Diagram Designator:

No common or grounded electrode (s)

#### Capacitance Value Per Section:

1000.000 picofarads single section

### Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

### Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

0.0 single section

### Nonderated Continuous Voltage Rating And Type Per Section:

50.0 dc single section

### Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:

-50.0/+50.0 single section

### **Tolerance Range Per Section:**

-2.00/+2.00 percent single section

### Case Material:

Plastic

# Insulation Resistance At Reference Temp:

100000.0 megohms

# Dissipation Factor At Reference Tempurature In Percent:

0.3000

# **Terminal Surface Treatment:**

Solder

### **Terminal Type And Quantity:**

2 uninsulated wire lead

Shelf Life:

N/a

#### Unit Of Measure:

---

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0