NSN 5910-00-009-1242

Glass Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-009-1242 **Body Style:** Piston **Overall Length:** 1.328 inches **Bushing Diameter:** 0.193 inches **Bushing Length:** 0.281 inches **Body Length:** 0.922 inches **Overall Diameter:** 0.312 inches Tempurature Coefficient Of Capacitance Range In Ppm Per Deg Celsius: -150.0/+150.0 single section **Quality Factor At 25 Deg Celsius:** 350.0 **Mounting Facility Screw Thread Series Designator:** Unf **Inclosure Type:** Encased **Adjustment Device Torque:** Between 1.000 inch-ounces and 10.000 inch-ounces **Bushing Shape:** Round w/flat Insulation Dc Resistance At 25 Deg Celsius: 1000.0 gigohms **Insulation Dc Resistance At Max Operating Temp:** 100000.0 megohms **Bushing Width:** 0.173 inches **Mounting Facility Type And Quantity:** 1 threaded bushing **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius **Thread Size:** 0.190 inches

Capacitance Range In Picofarads:

+1.0/+52.0 single section

Nonderated Voltage Rating And Type:

1000.0 dc continuous single section

Adjustment Device Drive Type And Quantity:

1 slotted screw

NSN 5910-00-009-1242

Glass Dielectric Variable Capacitor - Page 2 of 2



Capacitance Drift In Picofarads:

0.26 single section

Test Data Document:

81349-mil-c-14409 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity	Terminal	Type	And	Quantity
----------------------------	----------	------	-----	----------

1 turret

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A096a0