

View Online at <https://aerobasegroup.com/nsn/5910-00-009-2806>

Body Style:

W/thd bushing mtg, terminals on opposite end

Reliability Indicator:

Not established

Width Across Flats:

0.625 inches

Body Length:

2.170 inches

Continuous Current Rating In Amps:

15.0

Schematic Diagram Designator:

Feedthrough

Mounting Facility Screw Thread Series Designator:

Unf

Section Quantity:

1

Features Provided:

Mounting hardware and hermetically sealed case

Capacitance Value Per Section:

0.135 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Thread Size:

0.438 inches

Nonderated Continuous Voltage Rating And Type Per Section:

100.0 dc single section

Tolerance Range Per Section:

-25.00/+50.00 percent single section

Case Material:

Metal

Dissipation Factor At Reference Temperature In Percent:

3.0000

Test Data Document:

04655-43-553249 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

2 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0