## NSN 5910-00-012-3172

Paper Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-012-3172

view Offline at https://defobasegroup.com/nsn/0910-00-012-0112
Body Style:
W/o mtg facilities, terminal (s) on one surface
Reliability Indicator:
Not established
Terminal Length:
0.750 inches
Body Length:
2.500 inches
Body Width:
1.188 inches
Body Height:
3.875 inches
Center To Center Distance Between Terminals Parallel To Length
1.125 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Internal Electrical Connection Type:
Extended foil
Features Provided:
Hermetically sealed case
Insulation Resistance At Maximum Operating Temp:
1500.0 megohm-microfarads
Capacitance Value Per Section:
4.000 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
600.0 dc single section
Tolerance Range Per Section:
-10.00 to 10.00 percent single section
Case Material:
Metal
Insulation Resistance At Reference Temp:
2000.0 megohm-microfarads
Dissipation Factor At Reference Tempurature In Percent:
1.000
Power Factor At Reference Tempurature In Percent:
2.000
Terminal Surface Treatment:
Solder

2 tab, solder lug

**Terminal Type And Quantity:** 

## NSN 5910-00-012-3172

Paper Dielectric Fixed Capacitor - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0