## NSN 5910-00-012-5034

Ceramic Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-012-5034 **Thread Class:** 2a **Body Style:** Piston **Overall Length:** 0.562 inches **Bushing Diameter:** 0.250 inches **Bushing Length:** 0.250 inches **Body Length:** 0.312 inches **Overall Diameter:** 0.250 inches **Tolerance Of Tempurature Coefficient In Ppm Per Deg Celsius:** -50.0 to 50.0 single section **Quality Factor At 25 Deg Celsius:** 500.0 **Mounting Facility Screw Thread Series Designator:** Unef **Inclosure Type:** Encased **Adjustment Device Torque:** Between 2.000 inch-ounces and 4.000 inch-ounces **Bushing Shape:** Round w/flat Insulation Dc Resistance At 25 Deg Celsius: 10.0 megohms **Bushing Width:** Between 0.220 inches and 0.230 inches **Mounting Facility Type And Quantity:** 1 threaded stud Thready Qty Per Inch (tpi): 32 **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius **Thread Size:** 0.250 inches Capacitance Range In Picofarads:

+0.8 to 4.5 single section

**Nonderated Voltage Rating And Type:** 

750.0 dc continuous single section

NSN 5910-00-012-5034 Ceramic Dielectric Variable Capacitor - Page 2 of 2



Adjustment Device Drive Type And Quantity:
1 slotted screw
Terminal Type And Quantity:
1 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A096a0