

View Online at https://aerobasegroup.com/nsn/5910-00-013-9117

### **Body Style:**

W/o mtg facilities terminal (s) on one surface

### **Reliability Indicator:**

Established

## **Terminal Length:**

1.250 inches

### **Body Length:**

0.190 inches

#### **Body Width:**

0.190 inches

#### **Body Height:**

#### 0.090 inches

### Center To Center Distance Between Terminals Parallel To Length:

0.200 inches

#### **Terminal Diameter:**

0.025 inches

### Schematic Diagram Designator:

No common or grounded electrode (s)

### Capacitance Value Per Section:

56.000 picofarads single section

### Voltage Tempurature Limits Per Section In Percent Capacitance Change:

-25.0/+15.0 with rated voltage applied single section

### Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

#### Nonderated Continuous Voltage Rating And Type Per Section:

200.0 dc single section

#### **Tolerance Range Per Section:**

-10.00 to 10.00 percent single section

#### **Case Material:**

Ceramic

#### Insulation Resistance At Reference Temp:

1000.0 megohm-microfarads

### **Dissipation Factor At Reference Tempurature In Percent:**

2.5000

# **Terminal Surface Treatment:**

Solder

### **Test Data Document:**

81349-mil-c-39014 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Terminal Type And Quantity:**

2 uninsulated wire lead

#### **Specification Data:**

81349-mil-c-39014/1b government specification



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0