

View Online at https://aerobasegroup.com/nsn/5910-00-013-9432

## **Body Style:**

W/o mtg facilities, axial terminals

**Reliability Indicator:** 

Not established

**Terminal Length:** 

1.250 inches

## **Body Diameter:**

0.090 inches

**Body Length:** 

0.160 inches

#### **Terminal Diameter:**

0.016 inches

## Schematic Diagram Designator:

No common or grounded electrode (s)

## Insulation Resistance At Maximum Operating Temp:

1000.0 megohms

## **Capacitance Value Per Section:**

3900.000 picofarads single section

# Voltage Tempurature Limits Per Section In Percent Capacitance Change:

-25.0/+15.0 with rated voltage applied single section

# Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

## Nonderated Continuous Voltage Rating And Type Per Section:

100.0 dc single section

#### **Tolerance Range Per Section:**

-10.00/+10.00 percent single section

#### **Case Material:**

Ceramic

Insulation Resistance At Reference Temp:

10000.0 megohms

# Dissipation Factor At Reference Tempurature In Percent:

2.5000

# Power Factor At Reference Tempurature In Percent:

3.0000

#### **Terminal Surface Treatment:**

Solder

## **Test Data Document:**

81349-mil-c-11015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### **Terminal Type And Quantity:**

2 uninsulated wire lead

#### **Specification Data:**

81349-mil-c-11015/20 government specification



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0