## NSN 5910-00-020-6006

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-020-6006 **Body Style:** W/o mtg facilities, axial terminals Reliability Indicator: Not established **Terminal Length:** 1.500 inches **Body Diameter:** 0.297 inches **Body Length:** 0.687 inches **Terminal Diameter:** 0.025 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Features Provided:** Hermetically sealed case **Insulation Resistance At Maximum Operating Temp:** 5.0 megohm-microfarads **Capacitance Value Per Section:** 0.001 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 600.0 dc single section **Tolerance Range Per Section:** -25.00/+25.00 percent single section **Case Material:** Metal **Insulation Resistance At Reference Temp:** 2000.0 megohm-microfarads **Dissipation Factor At Reference Tempurature In Percent:** 1.2500 **Terminal Surface Treatment:** Solder **Case Insulation Material: Plastic Terminal Type And Quantity:** 2 uninsulated wire lead Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5910-00-020-6006

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0