

View Online at <https://aerobasegroup.com/nsn/5910-00-020-8007>

Body Style:

W/thd mtg hol (s)/stud(s), terminal(s) on one surface

Reliability Indicator:

Not established

Terminal Length:

0.250 inches

Body Length:

4.120 inches

Body Width:

1.050 inches

Body Height:

2.535 inches

Center To Center Distance Between Terminals Parallel To Length:

3.940 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 1.125 inches and 1.875 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

0.440 inches

Schematic Diagram Designator:

One terminal common to each section

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 0.593 inches and 0.656 inches

Mounting Facility Screw Thread Series Designator:

Unc

Mounting Facility Type And Quantity:

10 threaded mounting holes

Section Quantity:

9

Insulation Resistance At Maximum Operating Temp:

25.0 megohm-microfarads

Capacitance Value Per Section:

0.005 microfarads 2nd section

Nonderated Operating Temp:

Between -65.0 degrees celsius and 125.0 degrees celsius

Thread Size:

0.112 inches

Nonderated Continuous Voltage Rating And Type Per Section:

1500.0 dc 3rd section

Tolerance Range Per Section:

-10.00 to 10.00 percent all sections

Case Material:

Plastic

Insulation Resistance At Reference Temp:

5000.0 megohm-microfarads

Dissipation Factor At Reference Temperature In Percent:

0.005

Terminal Type And Quantity:

10 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0