## NSN 5910-00-020-8007

Mica Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-020-8007

Body	Style:	
Dogs	OLYIC.	

W/thd mtg hol (s)/stud(s), terminal(s) on one surface

**Reliability Indicator:** 

Not established

**Terminal Length:** 

0.250 inches

**Body Length:** 

4.120 inches

**Body Width:** 

1.050 inches

**Body Height:** 

2.535 inches

**Center To Center Distance Between Terminals Parallel To Length:** 

3.940 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 1.125 inches and 1.875 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

0.440 inches

**Schematic Diagram Designator:** 

One terminal common to each section

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 0.593 inches and 0.656 inches

**Mounting Facility Screw Thread Series Designator:** 

Unc

**Mounting Facility Type And Quantity:** 

10 threaded mounting holes

**Section Quantity:** 

**Insulation Resistance At Maximum Operating Temp:** 

25.0 megohm-microfarads

**Capacitance Value Per Section:** 

0.005 microfarads 2nd section

**Nonderated Operating Temp:** 

Between -65.0 degrees celsius and 125.0 degrees celsius

**Thread Size:** 

0.112 inches

Nonderated Continuous Voltage Rating And Type Per Section:

1500.0 dc 3rd section

**Tolerance Range Per Section:** 

-10.00 to 10.00 percent all sections

**Case Material:** 

**Plastic** 

NSN 5910-00-020-8007 Mica Dielectric Fixed Capacitor - Page 2 of 2



Insulation Resistance At Reference Temp:
5000.0 megohm-microfarads
Dissipation Factor At Reference Tempurature In Percent:
0.005
Terminal Type And Quantity:
10 solder stud
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A010b0