## NSN 5910-00-022-2848

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-022-2848

**Body Style:** W/thd mtg studs, axial terminals **Reliability Indicator:** Established **Body Diameter:** 0.670 inches **Body Length:** 1.625 inches **Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:** 0.375 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Mounting Facility Screw Thread Series Designator:** Unc **Mounting Facility Type And Quantity:** 2 threaded mounting studs **Features Provided:** Mounting hardware and hermetically sealed case **Capacitance Value Per Section:** 0.220 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 105.0 degrees celsius **Thread Size:** 0.138 inches Nonderated Continuous Voltage Rating And Type Per Section: 400.0 dc single section **Tolerance Range Per Section:** -10.00 to 10.00 percent single section **Case Material:** Metal **Insulation Resistance At Reference Temp:** 50000.0 megohms **Dissipation Factor At Reference Tempurature In Percent:** 0.3000 **Terminal Surface Treatment:** Solder **Case Insulation Material:** Plastic **Test Data Document:** 10001-2635193-1 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

2 tab, solder lug

**Terminal Type And Quantity:** 

## NSN 5910-00-022-2848

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Shelf Life:
-------------

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0