NSN 5910-00-023-2132

Body Style:

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-023-2132

W/o mtg facilities, axial terminalsw/o mtg facilities, axial terminalsw/o mtg facilities, axial terminals

Reliability Indicator:
Not establishednot established
Terminal Length:
1.500 inches 1.500 inches 1.500 inches
Body Diameter:
0.287 inches
Body Length:
0.875 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Anode Type:
Plain foil
Impedance At Minimum Operating Tempurature In Ohms:
1660.0
Electrical Polarization:
Polarized
Capacitance Value Per Section:
1.000 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Dc Leakage At Maximum Operating Temp:
50.0 milliamperes
Nonderated Continuous Voltage Rating And Type Per Section:
200.0 dc single section
Tolerance Range Per Section:
-15.00/+15.00 percent single section
Case Material:
Metal
Capacitive Electrode Material:
Tantalum
Power Factor At Reference Tempurature In Percent:
6.0000
Dc Leakage At Reference Temp:
10.000 microamperes
Terminal Type And Quantity:
2 uninsulated wire lead
Shelf Life:

--

N/a

Unit Of Measure:

NSN 5910-00-023-2132

Electrolytic Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0