## NSN 5910-00-024-0716



Electrolytic Fixed Capacitor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5910-00-024-0716 **Body Style:** W/o mtg facilities terminal (s) on one surface Reliability Indicator: Not established **Terminal Length:** 1.625 inches **Body Length:** 0.190 inches **Body Width:** 0.235 inches **Body Height:** 0.105 inches Center To Center Distance Between Terminals Parallel To Length: Between 0.105 inches and 0.145 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Anode Type:** Solid **Electrical Polarization:** Nonpolarized **Capacitance Value Per Section:** 0.330 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Dc Leakage At Maximum Operating Temp: 15.0 milliamperes Nonderated Continuous Voltage Rating And Type Per Section: 35.0 dc single section **Tolerance Range Per Section:** 

-10.00 to 10.00 percent single section

Case Material:

**Plastic** 

**Capacitive Electrode Material:** 

**Tantalum** 

**Dissipation Factor At Reference Tempurature In Percent:** 

6.0000

Dc Leakage At Reference Temp:

1.000 microamperes

**Terminal Surface Treatment:** 

Solder

**Terminal Type And Quantity:** 

2 uninsulated wire lead

## NSN 5910-00-024-0716

Electrolytic Fixed Capacitor - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0