## NSN 5910-00-024-0738

Air Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-024-0738 **Thread Class:** 2a **Body Style:** Piston **Overall Length:** 0.469 inches **Bushing Diameter:** 0.234 inches **Bushing Length:** 0.141 inches **Body Length:** 0.281 inches **Overall Diameter:** 0.281 inches Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius: 0.0 single section **Tolerance Of Tempurature Coefficient In Ppm Per Deg Celsius:** -50.0 to 50.0 single section **Quality Factor At 25 Deg Celsius:** 1500.0 **Mounting Facility Screw Thread Series Designator:** Uns **Inclosure Type:** Encased **Tuning Characteristic:** Straight line capacity single section **Adjustment Device Torque:** Between 0.500 inch-ounces and 5.000 inch-ounces **Bushing Shape:** Round Insulation Dc Resistance At 25 Deg Celsius: 1000.0 gigohms **Mounting Facility Type And Quantity:** 1 threaded bushing Thready Qty Per Inch (tpi): **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius **Thread Size:** 0.234 inches

**Capacitance Range In Picofarads:** 

+1.0 to 14.0 single section

## NSN 5910-00-024-0738

Air Dielectric Variable Capacitor - Page 2 of 2



| Nonderated Voltage Rating And Type:        |
|--|
| 250.0 dc continuous single section         |
| Adjustment Device Drive Type And Quantity: |
| 1 slotted screw                            |
| Terminal Type And Quantity:                |
| 1 turret                                   |
| Shelf Life:                                |
| N/a  |
| Unit Of Measure:                           |
|  |
| Demilitarization:                          |
| No   |

**Fiig:** A096a0