

View Online at <https://aerobasegroup.com/nsn/5910-00-027-7399>

Body Style:

W/o mtg facilities, axial terminals/w/o mtg facilities, axial terminals

Reliability Indicator:

Not established/not established

Terminal Length:

2.250 inches/2.250 inches

Body Diameter:

0.313 inches

Body Length:

0.672 inches

Terminal Diameter:

0.025 inches

Schematic Diagram Designator:

Electrod (s) grounded to case, w/gnd terminal

Anode Type:

Solid

Impedance At Minimum Operating Temperature In Ohms:

60.0

Electrical Polarization:

Polarized

Features Provided:

Hermetically sealed case

Capacitance Value Per Section:

68.000 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Dc Leakage At Maximum Operating Temp:

8.0 microamperes

Nonderated Continuous Voltage Rating And Type Per Section:

30.0 dc single section

Tolerance Range Per Section:

-20.00/+20.00 percent single section

Case Material:

Metal

Capacitive Electrode Material:

Tantalum

Dissipation Factor At Reference Temperature In Percent:

31.0000

Dc Leakage At Reference Temp:

1.000 microamperes

Terminal Surface Treatment:

Solder

Case Insulation Material:

Plastic

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A010b0