## NSN 5910-00-028-2078

Air Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-028-2078 **Thread Class:** 2a **Body Style:** Piston **Overall Length:** 0.485 inches **Bushing Diameter:** 0.120 inches **Bushing Length:** 0.156 inches **Body Length:** 0.266 inches **Overall Diameter:** 0.145 inches **Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius:** 0.0 single section **Tolerance Of Tempurature Coefficient In Ppm Per Deg Celsius:** -15.0 to 15.0 single section **Quality Factor At 25 Deg Celsius:** 10000.0 **Mounting Facility Screw Thread Series Designator:** Uns **Inclosure Type:** Encased **Tuning Characteristic:** Straight line capacity single section **Adjustment Device Torque:** Between 0.300 inch-ounces and 3.000 inch-ounces **Bushing Shape:** Round Insulation Dc Resistance At 25 Deg Celsius: 1000.0 gigohms **Mounting Facility Type And Quantity:** 1 threaded bushing Thready Qty Per Inch (tpi): **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius **Thread Size:** 0.120 inches

**Capacitance Range In Picofarads:** 

+0.3/+3.5 single section

NSN 5910-00-028-2078 Air Dielectric Variable Capacitor - Page 2 of 2



Nonderated Voltage Rating And Type:
250.0 dc continuous single section
Adjustment Device Drive Type And Quantity:
1 slotted screw
Terminal Type And Quantity:
1 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A096a0