NSN 5910-00-031-3719

Glass Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-031-3719 **Body Style:** Piston **Overall Length:** 0.312 inches **Bushing Diameter:** 0.194 inches **Bushing Length:** 0.250 inches **Body Length:** 0.531 inches **Overall Diameter:** 0.781 inches Tempurature Coefficient Of Capacitance Range In Ppm Per Deg Celsius: -50.0/+50.0 single section **Quality Factor At 25 Deg Celsius:** 500.0 **Mounting Facility Screw Thread Series Designator:** Unf **Inclosure Type:** Encased **Adjustment Device Torque:** Between 1.500 inch-ounces and 5.000 inch-ounces **Bushing Shape:** Round w/flat Insulation Dc Resistance At 25 Deg Celsius: 100.0 gigohms **Bushing Width:** 0.170 inches **Mounting Facility Type And Quantity:** 1 threaded bushing **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius **Thread Size:** 0.190 inches Capacitance Range In Picofarads: +1.0/+12.0 single section

Nonderated Voltage Rating And Type:

1000.0 dc continuous single section

Adjustment Device Drive Type And Quantity:

1 slotted screw

Terminal Type And Quantity:

1 turret

NSN 5910-00-031-3719

Glass Dielectric Variable Capacitor - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A096a0