## NSN 5910-00-032-9372

**Body Style:** 

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-032-9372

W/o mtg facilities, axial terminalsw/o mtg facilities, axial terminalsw/o mtg facilities, axial terminals						
Reliability Indicator:						
Not establishednot established						
Terminal Length:						
1.500 inches 1.500 inches 1.500 inches						
Body Diameter:						
0.201 inches						
Body Length:						
0.610 inches						
Terminal Diameter:						
0.025 inches						
Schematic Diagram Designator:						
No common or grounded electrode (s)						
Anode Type:						
Plain foil						
Electrical Polarization:						
Polarized						
Features Provided:						

15.000 microfarads single section

Hermetically sealed case

**Nonderated Operating Temp:** 

**Capacitance Value Per Section:** 

Between -80.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

20.0 dc single section

**Tolerance Range Per Section:** 

-20.00/+20.00 percent single section

Case Material:

Metal

**Capacitive Electrode Material:** 

Tantalum

**Dissipation Factor At Reference Tempurature In Percent:** 

6.0000

Dc Leakage At Reference Temp:

4.000 microamperes

**Terminal Surface Treatment:** 

Solder

**Case Insulation Material:** 

Plastic

**Terminal Type And Quantity:** 

2 uninsulated wire lead

## NSN 5910-00-032-9372

Electrolytic Fixed Capacitor - Page 2 of 2



_			-		
C	hο	14		.ife	
•			_	.II C	-

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0