NSN 5910-00-040-8756

W/o mtg facilities, terminal (s) on one surface

Body Style:

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-040-8756

Reliability Indicator:
Not established
Body Length:
1.312 inches
Body Width:
0.750 inches
Body Height:
2.500 inches
Schematic Diagram Designator:
Electrod (s) grounded to case, w/gnd terminal
Anode Type:
Etched foil
Electrical Polarization:
Polarized
Capacitance Value Per Section:
350.000 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Dc Leakage At Maximum Operating Temp:
920.0 milliamperes
Nonderated Continuous Voltage Rating And Type Per Section:
75.0 dc single section
Criticality Code Justification:
7
Zzzy
Tolerance Range Per Section:
Tolerance Range Per Section:
Tolerance Range Per Section: -15.00 to 75.00 percent single section
Tolerance Range Per Section: -15.00 to 75.00 percent single section Case Material:
Tolerance Range Per Section: -15.00 to 75.00 percent single section Case Material: Metal
Tolerance Range Per Section: -15.00 to 75.00 percent single section Case Material: Metal Capacitive Electrode Material:
Tolerance Range Per Section: -15.00 to 75.00 percent single section Case Material: Metal Capacitive Electrode Material: Tantalum
Tolerance Range Per Section: -15.00 to 75.00 percent single section Case Material: Metal Capacitive Electrode Material: Tantalum Power Factor At Reference Tempurature In Percent:
Tolerance Range Per Section: -15.00 to 75.00 percent single section Case Material: Metal Capacitive Electrode Material: Tantalum Power Factor At Reference Tempurature In Percent: 15.0000
Tolerance Range Per Section: -15.00 to 75.00 percent single section Case Material: Metal Capacitive Electrode Material: Tantalum Power Factor At Reference Tempurature In Percent: 15.0000 Dc Leakage At Reference Temp:
Tolerance Range Per Section: -15.00 to 75.00 percent single section Case Material: Metal Capacitive Electrode Material: Tantalum Power Factor At Reference Tempurature In Percent: 15.0000 Dc Leakage At Reference Temp: 92.000 microamperes
Tolerance Range Per Section: -15.00 to 75.00 percent single section Case Material: Metal Capacitive Electrode Material: Tantalum Power Factor At Reference Tempurature In Percent: 15.0000 Dc Leakage At Reference Temp: 92.000 microamperes Terminal Surface Treatment:
Tolerance Range Per Section: -15.00 to 75.00 percent single section Case Material: Metal Capacitive Electrode Material: Tantalum Power Factor At Reference Tempurature In Percent: 15.0000 Dc Leakage At Reference Temp: 92.000 microamperes Terminal Surface Treatment: Solder
Tolerance Range Per Section: -15.00 to 75.00 percent single section Case Material: Metal Capacitive Electrode Material: Tantalum Power Factor At Reference Tempurature In Percent: 15.0000 Dc Leakage At Reference Temp: 92.000 microamperes Terminal Surface Treatment: Solder Terminal Type And Quantity:

NSN 5910-00-040-8756

Electrolytic Fixed Capacitor - Page 2 of 2



_				
c	hο	JIF.		ife:
J	116		_	HG.

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0