NSN 5910-00-044-5513

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-044-5513

| Body Style: |
|--|
| W/o mtg facilities, terminal (s) on one surfacew/o mtg facilities, terminal(s) on one surfacew/o mtg facilities, terminal(s) on one surfacew |
| Reliability Indicator: |
| Not establishednot established |
| Body Length: |
| 1.305 inches |
| Body Width: |
| 0.720 inches |
| Body Height: |
| 2.000 inches |
| Schematic Diagram Designator: |
| Electrod (s) grounded to case, w/gnd terminal |
| Anode Type: |
| Solid |
| Impedance At Minimum Operating Tempurature In Ohms: |
| 2.8 |
| Electrical Polarization: |
| Polarized |
| Features Provided: |
| Hermetically sealed case |
| Capacitance Value Per Section: |
| 1000.000 microfarads single section |
| Nonderated Operating Temp: |
| Between -55.0 degrees celsius and 85.0 degrees celsius |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 45.0 dc single section |
| Tolerance Range Per Section: |
| -10.00/+10.00 percent single section |
| Case Material: |
| Metal |
| Capacitive Electrode Material: |
| Tantalum |
| Equivalent Series Resistance At Reference Tempurature In Ohms: |
| 0.25 |
| Terminal Type And Quantity: |
| 2 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

No

Demilitarization:

NSN 5910-00-044-5513

Electrolytic Fixed Capacitor - Page 2 of 2



Fiig:

A010b0