Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-045-4104

# Body Style:

W/thd mtg hole/stud, terminal (s) on one end

**Reliability Indicator:** 

Not established

# Width Across Flats:

0.312 inches

## **Terminal Length:**

0.140 inches

## Body Diameter:

0.312 inches

Body Length:

0.876 inches

## **Terminal Diameter:**

0.109 inches

# Schematic Diagram Designator:

Electrod (s) grounded to case

# Mounting Facility Screw Thread Series Designator:

Unf

### Mounting Facility Type And Quantity:

1 threaded mounting studs

### Capacitance Value Per Section:

100.000 picofarads single section

### Voltage Tempurature Limits Per Section In Percent Capacitance Change:

-25.0/+15.0 with rated voltage applied single section

### Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

### Thread Size:

0.250 inches

### Nonderated Continuous Voltage Rating And Type Per Section:

500.0 dc single section

### **Tolerance Range Per Section:**

-10.00/+10.00 percent single section

### Case Material:

Ceramic

### Insulation Resistance At Reference Temp:

20000.0 megohms

### **Dissipation Factor At Reference Tempurature In Percent:**

1.5000

# **Terminal Surface Treatment:**

Solder

# Test Data Document:

81349-mil-c-11015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



## Terminal Type And Quantity:

1 solder stud

### Specification Data:

81349-mil-c-11015/14 government specification

Shelf Life:

N/a

## Unit Of Measure:

---

## Demilitarization:

No

Fiig:

A010b0