## NSN 5910-00-050-7114

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-050-7114

**Body Style:** 

W/mtg tabs/flanges, terminal (s) on one surface

Reliability Indicator:

Not established

**Terminal Length:** 

0.750 inches

**Body Length:** 

Between 1.938 inches and 2.062 inches

**Body Width:** 

Between 1.938 inches and 2.062 inches

**Body Height:** 

Between 0.938 inches and 1.062 inches

Center To Center Distance Between Terminals Parallel To Length:

1.062 inches

**Unthreaded Mounting Hole Diameter:** 

0.187 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

2.375 inches

**Schematic Diagram Designator:** 

No common or grounded electrode (s)

**Mounting Facility Type And Quantity:** 

2 unthreaded mounting holes

**Features Provided:** 

Hermetically sealed case

**Insulation Resistance At Maximum Operating Temp:** 

20000.0 megohm-microfarads

**Capacitance Value Per Section:** 

3.400 microfarads single section

**Nonderated Operating Temp:** 

Between 0.0 degrees celsius and 60.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

60.0 dc single section

**Tolerance Range Per Section:** 

-2.00/+2.00 percent single section

**Case Material:** 

Metal

Insulation Resistance At Reference Temp:

50000.0 megohm-microfarads

**Terminal Surface Treatment:** 

Solder

**Terminal Type And Quantity:** 

2 tab, solder lug

## NSN 5910-00-050-7114

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Shelf	Life:
N/a	

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0