Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-050-7114

Body Style:

W/mtg tabs/flanges, terminal (s) on one surface

Reliability Indicator:

Not established

Terminal Length:

0.750 inches

Body Length:

Between 1.938 inches and 2.062 inches

Body Width:

Between 1.938 inches and 2.062 inches

Body Height:

Between 0.938 inches and 1.062 inches

Center To Center Distance Between Terminals Parallel To Length:

1.062 inches

Unthreaded Mounting Hole Diameter:

0.187 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

2.375 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Mounting Facility Type And Quantity:

2 unthreaded mounting holes

Features Provided:

Hermetically sealed case

Insulation Resistance At Maximum Operating Temp:

20000.0 megohm-microfarads

Capacitance Value Per Section:

3.400 microfarads single section

Nonderated Operating Temp:

Between 0.0 degrees celsius and 60.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

60.0 dc single section

Tolerance Range Per Section:

-2.00/+2.00 percent single section

Case Material:

Metal

Insulation Resistance At Reference Temp:

50000.0 megohm-microfarads

Terminal Surface Treatment:

Solder

Terminal Type And Quantity:

2 tab, solder lug

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A010b0