

View Online at https://aerobasegroup.com/nsn/5910-00-051-5684

### **Body Style:**

W/thd mtg bushing, terminals on opposite ends

**Reliability Indicator:** 

Not established

## Width Across Flats:

0.313 inches

#### **Terminal Length:**

0.469 inches

#### **Body Length:**

0.750 inches

## **Terminal Diameter:**

0.051 inches

## Schematic Diagram Designator:

### Feedthrough

### Mounting Facility Screw Thread Series Designator:

Unc

## Mounting Facility Type And Quantity:

1 threaded bushing

## Capacitance Value Per Section:

4000.000 picofarads single section

### Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

### Thread Size:

0.250 inches

### Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

0.0 single section

### Nonderated Continuous Voltage Rating And Type Per Section:

500.0 dc single section

### Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:

-30.0/+30.0 single section

### **Tolerance Range Per Section:**

-20.00/+20.00 percent single section

### Case Material:

Metal

### Insulation Resistance At Reference Temp:

100000.0 megohms

### **Dissipation Factor At Reference Tempurature In Percent:**

2.0000

# **Terminal Surface Treatment:**

Solder

# Terminal Type And Quantity:

2 wire hook/loop



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0