## NSN 5910-00-051-9828

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-051-9828

Body	Style:
------	--------

W/o mtg facilities, axial terminalsw/o mtg facilities, axial terminalsw/o mtg facilities, axial terminals

### **Reliability Indicator:**

Not establishednot established

## **Terminal Length:**

2.250 inches 2.250 inches 2.250 inches

**Body Diameter:** 

0.390 inches

**Body Length:** 

0.828 inches

#### **Schematic Diagram Designator:**

No common or grounded electrode (s)

**Anode Type:** 

Solid

**Impedance At Minimum Operating Tempurature In Ohms:** 

42.0

**Electrical Polarization:** 

Polarized

#### **Capacitance Value Per Section:**

110.000 microfarads single section

## **Nonderated Operating Temp:**

Between -55.0 degrees celsius and 85.0 degrees celsius

#### Dc Leakage At Maximum Operating Temp:

11.0 milliamperes

## Nonderated Continuous Voltage Rating And Type Per Section:

25.0 dc single section

## **Tolerance Range Per Section:**

-15.00/+20.00 percent single section

**Case Material:** 

Metal

## **Capacitive Electrode Material:**

Tantalum

## **Equivalent Series Resistance At Reference Tempurature In Ohms:**

2.00

## Dc Leakage At Reference Temp:

2.000 microamperes

#### **Terminal Surface Treatment:**

Solder

## **Case Insulation Material:**

Plastic

## **Terminal Type And Quantity:**

2 uninsulated wire lead

# NSN 5910-00-051-9828

Electrolytic Fixed Capacitor - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0