NSN 5910-00-052-3276

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-052-3276

D	_	٦,		0	٠			
D	u	u	v	J	ιν	ш	e:	

W/o mtg facilities, terminal (s) on one surfacew/o mtg facilities, terminal(s) on one surfacew/o mtg facilities, terminal(s) on one surface

Reliability Indicator:

Not establishednot established

Body Length:

1.275 inches

Body Width:

0.750 inches

Body Height:

2.500 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Anode Type:

Etched foil

Electrical Polarization:

Polarized

Mounting Facility Screw Thread Series Designator:

Unc

Features Provided:

Mounting hardware and hermetically sealed case

Capacitance Value Per Section:

1400.000 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Thread Size:

0.138 inches

Dc Leakage At Maximum Operating Temp:

1220.0 milliamperes

Nonderated Continuous Voltage Rating And Type Per Section:

25.0 dc single section

Tolerance Range Per Section:

-45.00/+75.00 percent single section

Case Material:

Metal

Capacitive Electrode Material:

Tantalum

Dc Leakage At Reference Temp:

122.000 microamperes

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

NSN 5910-00-052-3276

Electrolytic Fixed Capacitor - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A010b0