Mica Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-052-3991

#### **Body Style:**

W/o mtg facilities terminal (s) on one surface

#### **Reliability Indicator:**

Not established

# **Terminal Length:**

1.000 inches

### **Body Length:**

0.375 inches

#### **Body Width:**

0.355 inches

#### **Body Height:**

#### 0.200 inches

### Center To Center Distance Between Terminals Parallel To Length:

0.150 inches

#### Schematic Diagram Designator:

No common or grounded electrode (s)

## Insulation Resistance At Maximum Operating Temp:

10000.0 megohms

## **Capacitance Value Per Section:**

270.000 picofarads single section

## Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

## Nonderated Continuous Voltage Rating And Type Per Section:

100.0 dc single section

### Tempurature Coefficient Of Capacitance Range Per Section In Ppm Per Deg Celsius:

+0.0 to 70.0 single section

### **Tolerance Range Per Section:**

-5.00 to 5.00 percent single section

### Case Material:

Plastic

### Insulation Resistance At Reference Temp:

100000.0 megohms

### **Terminal Surface Treatment:**

Solder

### **Terminal Type And Quantity:**

2 uninsulated wire lead

Shelf Life:

N/a

#### Unit Of Measure:

--

# Demilitarization:

No

# NSN 5910-00-052-3991

Mica Dielectric Fixed Capacitor - Page 2 of 2

**Fiig:** A010b0

