

View Online at <https://aerobasegroup.com/nsn/5910-00-052-4084>

Body Style:

W/thd mtg bushing, terminals on opposite ends

Reliability Indicator:

Not established

Width Across Flats:

0.313 inches

Terminal Length:

0.250 inches

Body Length:

0.625 inches

Schematic Diagram Designator:

Feedthrough

Mounting Facility Screw Thread Series Designator:

Unc

Mounting Facility Type And Quantity:

1 threaded bushing

Capacitance Value Per Section:

100.000 picofarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Thread Size:

0.216 inches

Temperature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

-1500.0 single section

Nonderated Continuous Voltage Rating And Type Per Section:

500.0 dc single section

Tolerance Of Temperature Coefficient Per Section In Ppm Per Deg Celsius:

-250.0/+250.0 single section

Tolerance Range Per Section:

-10.00/+10.00 percent single section

Case Material:

Metal

Insulation Resistance At Reference Temp:

50000.0 megohms

Power Factor At Reference Temperature In Percent:

0.6000

Terminal Surface Treatment:

Solder

Terminal Type And Quantity:

2 wire hook/loop

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0