

View Online at <https://aerobasegroup.com/nsn/5910-00-054-4241>

Body Style:

W/o mtg facilities, terminal (s) on one end/w/o mtg facilities, terminal(s) on one end/w/o mtg facilities, terminal(s) on one end

Reliability Indicator:

Not established/not established/not established

Terminal Length:

0.281 inches 0.281 inches 0.281 inches

Body Diameter:

Between 2.469 inches and 2.531 inches

Body Length:

Between 4.063 inches and 4.187 inches

Continuous Current Rating In Amps:

19.4

Center To Center Distance Between Terminals Parallel To Diameter:

Between 1.109 inches and 1.141 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Anode Type:

Plain foil

Impedance At Minimum Operating Temperature In Ohms:

1.0

Electrical Polarization:

Polarized

Capacitance Value Per Section:

44000.000 microfarads single section

Nonderated Operating Temp:

Between -40.0 degrees celsius and 65.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

27.5 dc single section

Tolerance Range Per Section:

-10.00/+100.00 percent single section

Case Material:

Metal

Capacitive Electrode Material:

Aluminum

Equivalent Series Resistance At Reference Temperature In Ohms:

0.033

Dc Leakage At Reference Temp:

2.000 microamperes

Case Insulation Material:

Plastic

Terminal Type And Quantity:

2 threaded hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0