## NSN 5910-00-055-8053

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-055-8053

| view Online at https://aerobasegroup.com/nsn/5910-00-055-8053  |
|--|
| Body Style:  |
| W/o mtg facilities, terminals on opposite surfaces   |
| Reliability Indicator:   |
| Not established  |
| Terminal Length:   |
| 0.850 inches   |
| Body Length:   |
| 0.500 inches   |
| Body Width:  |
| 0.500 inches   |
| Body Height:   |
| 0.090 inches   |
| Schematic Diagram Designator:  |
| No common or grounded electrode (s)  |
| Capacitance Value Per Section:   |
| 300.000 picofarads single section  |
| Nonderated Operating Temp:   |
| Between -40.0 degrees celsius and 125.0 degrees celsius  |
| Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:   |
| 95.0 single section  |
| Nonderated Continuous Voltage Rating And Type Per Section:   |
| 2500.0 dc single section   |
| Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:   |
| -25.0/+25.0 single section   |
| Tolerance Range Per Section:   |
| -5.00 to 5.00 percent single section   |
| Case Material:   |
| Glass  |
| Insulation Resistance At Reference Temp:   |
| 1000000.0 megohms  |
| Dissipation Factor At Reference Tempurature In Percent:  |
| 0.0200   |
| Quality Factor At Reference Temp:  |
| 3000.0000  |
| Terminal Surface Treatment:  |
| Silver   |
| Test Data Document:  |
| 14304-c11-0004 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. |
| excludes any specification, standard or other document that may be referenced in a basic governing drawing)                              |
| Terminal Type And Quantity:  |
| 2 ribbon   |

N/a

Shelf Life:

## NSN 5910-00-055-8053

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



|   |    | • • |             |          |  |
|---|----|-----|-------------|----------|--|
| ш | ın | 10  | <i>(</i> )+ | Measure: |  |
|   |    |     |             |          |  |

--

Demilitarization:

No

Fiig:

A010b0