

View Online at <https://aerobasegroup.com/nsn/5910-00-056-9851>

Body Style:

W/thd mtg hol (s)/stud(s) terminal(s) on one surface

Reliability Indicator:

Not established

Body Length:

1.750 inches

Body Width:

1.000 inches

Body Height:

2.438 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

2.062 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Mounting Facility Screw Thread Series Designator:

Unf

Mounting Facility Type And Quantity:

2 threaded mounting studs

Insulation Resistance At Maximum Operating Temp:

10000.0 megohm-microfarads

Capacitance Value Per Section:

0.250 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 100.0 degrees celsius

Thread Size:

0.190 inches

Temperature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

-100.0 single section

Nonderated Continuous Voltage Rating And Type Per Section:

400.0 dc single section

Tolerance Of Temperature Coefficient Per Section In Ppm Per Deg Celsius:

-20.0/+20.0 single section

Tolerance Range Per Section:

-10.00/+10.00 percent single section

Case Material:

Metal

Insulation Resistance At Reference Temp:

750000.0 megohm-microfarads

Dissipation Factor At Reference Temperature In Percent:

0.020

Dielectric Material:

Plastic polystyrene

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0